



EN Transfer units

ST diesel fuel transfer stations are the fruit of careful design and are a modern and economical solution for the private refueling sector. Easy to install, versatile and compact, they are used wherever it is necessary to fill mobile tanks or interact with the distribution unit. Stations equipped with meters provide an accurate measure of the product dispensed and allow a useful and practical periodic check on consumption. Stations are available in a complete range of flow capacities and motors to satisfy every need.

Equipment

Groups are available with various equipment as listed in the table. All are provided with aspiration filters, check valve with filter and gun support. The length of the dispensing tube is 6 meters. The ST group can be integrated with a metal housing to protect the components. All accessories necessary to complete the installation are also available.



ST with Meter and Filter

Flow rate up to **85 l/min**

Accuracy +/- **1%**



Available with:

AC pumps



Panther 56 E 80
Panther 72 E 120

Meters



K33

Nozzles



Automatic

Filters



Filter

Code	Description	Meter	Filter H2O	Flow rate		Pump							AC (DC)	Delivery pipe	Hose length mt	Suction hose mt	Nozzle	Weight Kg	
				l/min	gal/min	Viscomat 70	Viscomat 90	Panther 56 (72)	E 80	E 120	ByPass 2000	Panther DC							Bipump
F00386F00	ST P56 Filtre	K33	•	52	14	-	-	•	-	-	-	-	-	230/50	3/4"G	6	4	A	25
F00265F00	ST P72 Filtre	K33	•	70	18	-	-	•	-	-	-	-	-	230/50	3/4"G	6	4	A	26
F00395F00	ST E120 Filtre	K33	•	85	22	-	-	-	-	•	-	-	-	230/50	1"G	6	4	A	32

Packaging: mm 580x380x320 with suction hose 4 meters. The units can also be supplied for operating under different voltages.